

## CASSETTE BL : 24 Fiber Splice Tray 22.5x11.5x2.5 cm



### Product Description

24 Fiber Splice Tray with tilting, comes with fibre holder for 24 Splice Sleeves. Can be stacked and is suitable for most types of patch panels and cabinets. It is designed with a view for troubleshooting and protection of the fiber since there is plenty of room for the retraction of surplus fiber.

|                     |  |                     |   |
|---------------------|--|---------------------|---|
| Material            | ABS Flame (add Length)                     | Color               | White   |
| Capacity            | 24 fibers                                  | Size                | 22.5x11.5x2.5 cm  |
| Life                | 1000 times                                 | Tensile strength    | >1000N  |
| Connector loss      | ≤0.5dB                                     | Back wave loss      | PC≥40dB, UPC≥50dB, APC≥60dB   |
| Working wavelength  | 850, 1310, 1550nm                          | Working temperature | -40°C+55°C  |
| Relative humidity   | ≤ 85% (30°)                                | Air pressure        | 70Kpa~106Kpa  |
| Sealing performance | Remain unchanged for 72h on pressure 70kpa | Application         | Fiber Splice Enclosure, Fiber Termination Box, Cable Distribution Box |

### Product Features

- Can be stacked up to 2 pieces in a 1U high density
- Supplied with holders for Splice sleeves
- Easy retraction of surplus fiber
- Optional Hang for “book system”, for all sides
- Fiber and loose tube entry possibilities from all four sides
- Standard fixing points
- Easy repair and maintenance
- Halogen free and flame-retardant