

30mw

# Visual Fault Locator

Standard 2.5mm interface,  
Applicable to SC/FC  
/ST/LC (optional)

Location of breakpoint

Strong light source

Supports multiple  
connectors



# High quality pen head Stable performance

Powerful light source,  
quick mastery of monopoly,  
time-saving and efficient



Tips: Do not look directly  
at the light source,  
Avoid eye damage

**Distributeur** SARL ALIEF lot n°: 1, Gpe 13, Hamiz, Dar El Beida, Alger std : ooredoo: 0560.271.399 , 0560.261.451 mobilis:  
0661.528.551

Tel fix : +213 (0) 23 858 510 /11, (0)23 865001 Fax : +213 (0) 23 858 514 web: [www.alief.dz](http://www.alief.dz) emails: [com@alief.dz](mailto:com@alief.dz), [com@alief-dz.com](mailto:com@alief-dz.com)  
[dz.com](http://dz.com) Page 2



# Supports multiple optical fiber interfaces

Standard 2.5mm interface,  
Applicable to SC/FC/ST/LC (optional)



**Note: The adapter is not standard**

If it is necessary to check the 1.25 mm LC interface FC-LC adapter shall be purchased separately

**FC male to LC female adapter**

## Easily penetrate long distance optical fiber

High performance light emitting head, Light beam concentration and divergence are small



**Distributeur** SARL ALIEF lot n°: 1, Gpe 13, Hamiz, Dar El Beida, Alger std : ooredoo: 0560.271.399 , 0560.261.451 mobilis: 0661.528.551

Tel fix : +213 (0) 23 858 510 /11, (0)23 865001 Fax : +213 (0) 23 858 514 web: [www.alief.dz](http://www.alief.dz) emails: [com@alief.dz](mailto:com@alief.dz), [com@alief-dz.com](mailto:com@alief-dz.com) Page 4

# Replaceable ceramic core Take off the metal head when replacing

Accessories can be  
purchased separately



2.5mm  
Metal head



7mm  
Ceramic core

Click to buy>>



Tips: Ceramic core is fragile,  
It cannot be installed and removed by force

Anti slip handle,  
comfortable  
to handle

Sliding block switch design,  
Control the state of  
the red pen as you like

Sliding upward  
means "Changliang",  
while sliding downward  
means "flashing"



# Introduction to product structure

Metal battery cartridge

Protective cap

Battery cover

Sliding cover switch

# Product parameters

Product name	Visual Fault Locator
Output optical power	>30mW
Output Wavelength	650nm $\pm$ 10nm
Fiber optic adapter	2.5mm universal connector
Service temperature	0~+60°C
Storage temperature	-20~+70°C
Battery Type	2 No.5 alkaline batteries
Battery Life	>9 hour
shape	17.5x2x2cm
weight	70g

