

## Optic Fiber Splice Closure 72 cores MANCH.FO.72



### Features:

MANCH.FO.72 Splice Closure

Maximum capacity: 120 core

Seal way: Rubber ring The use of high-strength engineering plastic shell that can endure harsh conditions such as vibration, impact, tensile cable distortion and strong temperature changes The use of reusable components to open seal in order to ensure a good airtight waterproof performance. Does not require special tools, easy to install and open the duplicate.

The scope of application : aerial, direct-buried, wall-mounting, duct-mounting,










The application of temperature : -40°C ~ 75°C

IP grade: IP 68

### Specifications:

Type	MANCH.FO.72
Product outlook size	450×180×130 (mm)
Product material quality	PPR or ABS
Product weight	Approximately 1.5 kg
Suitable Dia of cable	Φ10~Φ22
No. of Cable Inlet/Outlet	4
Fibers/Tray	12 or 24 F
Max capacity(F)	120fibers
Each packing quantity	10 pieces

**Accessories:**

Item	Type	Picture	Quantity
Heat shrinkable tube	60mm or 40mm		Allocated by the number of fibers
Sticky cincture	wider		1 pcs
Sticky cincture	narrow		2 pcs
Sealing washer			8 PCS
Hanging hook			2 pcs
block			2 pcs
Screw	Stainless steel		12 pcs
Insulated tape			1 pcs
Sealing rubber ring			2 pcs

Allen wrench	MS		1 pcs
--------------	----	--	-------