

## 6 Ports 100M PoE Switch with Build-in Power Supply

Model: TS-SF1204P-250M with extend 300meter distance

- 4\*10/100M + 2\*100MRJ45 Port PoE Switch,1-4 ports support to AF/AT;
- Comply with IEEE 802.3, IEEE 802.3u standards;
- Support 10M/250 meters long distance transmission&Vlan;
- PoE port support AF/AT intelligent recognition. Standard power is 15.4W/port,Maximum power: 30W/port;
- Supports POE devices such as wireless access points (APs) and network surveillance cameras through Category 5/6 Ethernet cables;
- The power supply total is 60W;



Model	TS-SF1204P-250M
Fixed Port	4*10/100Base-T/TX PoE ports (Data/Power) 2*10/100Base-T/TX Uplink RJ45 ports (Data)
POE Port	Port 1-4 support PoE
Feature	The port 1-4 support 10M/250 meters long distance transmission and Vlan
Network Protocol	IEEE802.3 10BASE-T; IEEE802.3i 10Base-T; IEEE802.3u 100Base-TX; IEEE802.3x.
Ethernet Port Feature	10/100Base-T(X) automatic detection, full/half Duplex MDI/MDI-X adaptive
Forwarding Mode	Store and Forward(Full Wire Speed)
Switching Capacity	1.2Gbps
MAC	2K
Forwarding Rate	0.89Mpps
Buffer Memory	768K
Twisted Pair Transmission	10BASE-T:Cat5 UTP(≤250 meter) 100BASE-TX:Cat5 or later UTP(≤100 meter)
Power Supply Pin	Default 1/2(+), 3/6(-);
MAX / AVERAGE Power Per Port	30W/15.4W
Total PWR / Input Voltage	60W (52V)
Power Consumption	Standby:<2W;Full load:<60W
LED Indicator	Power indicator: PWR (Green); Network indicator: 1-4(Link/Act)/ (Green),5-6(Link/Act)/ (Green), Extend Function indicator: (Green)
Power Supply	Build-in power adaptor AC100~240V 50-60Hz,60W

Operation TEMP / Humidity	-20~+55°C;5%~90% RH non condensing
Storage TEMP / Humidity	-40~+75°C;5%~95% RH non condensing
Dimension	220x140x45mm
Net /Gross Weight	<0.8kg / <1.2kg
Installation Method	desktop type, wall mounted
Protection	IEC61000-4-2(ESD): ±8kV contact discharge, ±15kV air discharge IEC61000-4-5(Lightning protection/Surge): Power:CM±4kV/DM±2kV; Port: ±4kV
Protection level	IP30
Certification	CCC;CE mark, commercial;CE/LVD EN60950; FCC Part 15 Class B;RoHS

Application

